

F5DQ41WMA2-P

4MP Smart AI Alert WDR Auto Focus indoor Network Vandalproof Dome Camera



Model Number	F5DQ41WMA2-P
Camera	
Image Sensor	1/2.8"SONY color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0Lux with IR on
Lens	Motorized 2.8-12mm lens , 4X optical zoom
Shutter Time	Auto(1/5 - 1/100000)
IR Distance	30m
IR LEDs	12pcs IR LEDs
White Balance	Auto / Manual
AGC	Support
WDR	128db REAL WDR
DNR	2D/3D DNR
BLC	Support
HLC	Support
Video	
Max. Image Resolution	4MP@25FPS

Video Compression	S265+/H265/H264
Frame Rate	Main code stream: 5MP/4MP/3MP/2MP@25fps/30fps Auxiliary stream: D1/VGA@25fps/30fps
Video Bit Rate	512Kbps-6144Kbps support self-adjustable as needed
Image Settings	Brightness,contrast,saturation,exposure,upside down,mirror adjustable
Bit Superposition	Support OSD name,time and date information superposition
Web Access	Internet explorer 6.0 and above (Web Server embedded in device) browser
Audio	
Audio Input	Support, built-in microphones
Audio Output	Support, built-in speaker
Audio Compression	G.711A/G.711U/64k
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP,UDP,HTTP,HTTPS,DHCP,RTSP,NTP,PPPOE
ONVIF	ONVIF2.6
APP	IOS, Android
PC	Support
System	
Alarm	Motion detection alarm
Storage	Optional
Motion Detection	22*18 windows motion detection areas can be setting
Area Occlusion Alarm	Support
Video Mask	Support
General	
Language Support	CHN(S)/CHN(T)/ENG
POE	IEEE802.3af
Power Supply	DC12V±10% /POE
Power Consumption	Max 6W
Lightning Protection	2KV
Housing	Vandalproof Dome
Weather Proof	IP67
Working Temperature	-30 °C to 85 °C
Working Humidity	10%-95% (Non-condensing)