

MP-B301I500M-WTA2

5X Zoom Smart Wifi Standalone SD I TF Card **PTZ** Dome Camera

Model Number	MP-B301I500M-WTA2
Camera	
Image Sensor	1/2.8" SONY color CMOS,Hisilicon
Min. Illumination	Color: 0.1Lux @F1.2, B/W: 0.01Lux with IR on
Lens	Auto-Focus 2.7-13.5mm lens,5X Optical Zoom
Shutter Time	Auto
IR Distance	40-50m
IR Board	6pcs IR array leds
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
BLC	Auto
HLC	Auto
Video	
Max. Image Resolution	5MP(2560x1920)@20fps
Frame Rate	Main code stream:5MP(2560x1920)@20fps,4MP(2560x1440)@20fps

	Auxiliary stream:800x448@20fps,640x352@20fps
Video Compression	H.265/H.264
Video Bit Rate	32Kbps-6144bps support self-adjustable as needed,default 1024Kbps
Image Settings	Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable
Bit Superposition	Support OSD name,time and date information superposition
Web Access	Support IE,Google,Firefox Browser
Pan & Tilt	
Pan Speed/Angle	Pan Speed:10°-20°/S,Speed Adjustable;Pan Angle:0°-355°
Tilt Speed/Angle	Tilt Speed:8°-25°/S,Speed Adjustable;Pan Angle:0°-90°
Audio	
Two-way Audio	Built-in Microphone and speaker
Audio Compression	G.711
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, TCP, ICMP,UDP,ARP,ICMP,SMTP,FTP,DHCP,DNS DDNS,NTP,UPNP,RTSP
WIFI	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
System	
Alarm I/O	Motion detection alarm
Storage	Max support 64GB SD card,timing video storage,motion detection video storage;
Motion Detection	4 windows motion detection areas can be setting(sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox,the pic and video be upload to FTP Server
General	
Working Temperature	-10 °C to 60 °C
Working Humidity	10%-95% (Non-condensing)
Power Supply	DC12V±10%
Power Consumption	Max 12W
Housing	Metal PTZ Dome
Weather Proof	IP66
Language Support	CHN(S)/CHN(T)/ENG/KOR/JPN