

MP-B306I216SL-WTA2

Smart Wifi SD Card 2.5 Inch Speed Dome Camera



Model	MP-B306I216SLM-WTA2
Camera	
Image Sensor	1/2.8" SONY color CMOS
Effective Pixels	2.0MP/1080P
Synchronization	Internal
Code Format	H265/H264
Code Rate	32Kbps~6144Kbps adjustable, default 1536kbps
Stream	Dual-stream
Frame Rate	Main code stream:1080P@25fps/30fps Auxiliary stream: D1/640x352@ 25/30fps
Min. Illumination	0.01LUX/F1.2 color,0.005LUX/F1.2 WITH IR ON (BW)
Day & Night Mode	Color/B&W/Intelligent model
Electronic Shutter	Auto
White Balance	Auto

AGC	Auto
WDR	Digital WDR
DNR	3D DNR
SNR	≥48dB
IR board	6PCS IR Array LEDs (4pcs IR LEDs, 2pcs white LEDs)
IR Distance	30m IR distance, 10m white colorful vision distance
PTZ	
Horizontal Angle	0-355°
Vertical Angle	0-90°
Pan Speed	0.1°-20°/S
Tilt Speed	0.1°-20°/S
Preset Point	7 preset points
cruise	Support
Functions	
Motion Detection	Support
Snapshot	Support
Email Alarm	Support
Audio Setting	People can make your voice record and automatically to tell the people who break into your area
Detection Alarm	When Detected people around, blue & red strobe flashing with audio
Alarm linkage	The mobile detection alarm is pushed to the APP Or device local sound alarm
Mirror Image	Flip horizontal/vertical
Voice Intercom	Built-in microphone and speaker
Storage	Built-in Micro SD card slot, Max128G, timer capture
Web Access	Support IE, Google, Firefox browser, Built-in webserver to facilitate the user to use the standard IE browser to achieve the front end of the real-time browsing and setting management
Lens	
Focal Length	3.6mm fix lens
Lens Megapixel	3 Megapixel fixed lens
NETWORK	
Network Interface	1*RJ45 10M/100M Ethernet Port
WIFI	WIFI 802.11b/g/n
AP	Support
P2P	Support Max 6users, browsing at the same time (each stream: 3 users)
Mobile Surveillance	iOS, Android
PC	Support
Interface	
Antenna	1 * WIFI

Storage	1PC Micro SD card
Reset	Support key reset
Ethernet	1PC RJ45
General	
Working Temperature	-30 °C to +60 °C
Working Humidity	10%-90% RH (Non-condensing)
Power Supply	DC12V2A
Lightning protection	GB/T17626.5, IEC61000-4-5
Power Consumption	Max 10W
Housing	Outdoor Metal Bullet
Weather Proof	IP67
Size	22.6*19.0*13.3 cm