

## MP-B405I216G2-G1TA, MP-B405I216G2-G2TA

Smart 4G Wifi 4.0 Inch Speed Dome Camera



Model (Euro)	MP-B405I216G2-G1TA
Model (US)	MP-B405I216H2-G2TA
<b>Camera</b>	
Image Sensor	1/2.8" SONY color CMOS
Effective Pixels	2.0MP/1080P
Code Format	H265/H264
Stream	Dual-stream
Code Rate	32Kbps~6144Kbps adjustable , default 1536kbps
Frame Rate	Main code stream:1080P@25fps/30fps Auxiliary stream: D1/640x352@ 25/30fps

Day & Night Mode	External control
Min. Illumination	0.05LUX/F1.6 color,0.09LUX/F1.6(BW)
Electronic Shutter	Auto
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
SNR	≥48dB
IR Distance	6PCS IR Array LEDs
IR Distance	80m
<b>PTZ</b>	
Horizontal Angle	0-355°
Vertical Angle	0-90°
Pan Speed	0.1°-40°/S
Tilt Speed	0.1°-40°/S
Preset Point	8 preset points
Line Scan	1 x AB line scan
<b>Functions</b>	
Motion Detection	Support
Snapshot	Support
Email Alarm	Support
Alarm linkage	The mobile detection alarm is pushed to the APP
Mirror Image	Flip horizontal/vertical
Audio	Support, built-in mic
Storage	Built-in Micro SD card slot, Max 128G, timer capture
Web Access	Support IE, Google, Firefox browser, Built-in webserver to facilitate the user to use the standard IE browser to achieve the front end of the real-time browsing and setting management(The computer is connected to a 4G hotspot)
<b>Lens</b>	
Focal Length	4.7-86.4mm
Optical Zoom	20X
Lens Megapixel	3 Megapixel fixed lens
<b>4G &amp; Wifi</b>	
SIM	Nano SIM Card
Antenna	1 x WIFI antenna and 2 x 4G antennas
WIFI	WiFi 802.11b/g/n
AP	Support
P2P	Support Max 6users, browsing at the same time (each stream: 3 users )
Mobile Surveillance	iOS, Android

Smart 4G Series | MP-B405I216G2-G1TA, MP-B405I216G2-G2TA **mapesen®**

PC	Support
4G Europe Standard(G1)	4G FDD-LTE: B1/B3/B7/B8/B20; 4G TDD-LTE: B38/B40/B41;
	3G WCDMA: B1/B8; 2G GSM/EDGE: 1800MHZ/900MHZ;
4G USA Standard(G2)	4G FDD-LTE: B1/B2/B4/B5/B12/B13/B17/B25/B26;
	3G WCDMA: B2/B4/B5; 2G GSM/EDGE:1800MHZ/900MHZ
<b>Interface</b>	
Storage	1pcs Micro SD card
WIFI	1pcs
4G	2pcs
reset	Support key reset
Ethernet	No
Audio output	1pcs RCA
<b>General</b>	
Working Temperature	-30 °C to +60 °C
Working Humidity	10%-90% RH (Non-condensing)
Power Supply	DC12V±10%
Lightning protection	GB/T17626.5, IEC61000-4-5
Power Consumption	Max 10W
Housing	Outdoor Metal Bullet
Weather Proof	IP67
Size	154x137x239mm