

MP-F1B4I206-WT

Smart Wifi Standalone SD I TF Card Vandalproof Dome Camera



Model Number		MP-F1B4I206-WT
Camera		
Image Sensor	1/2.9" color CMOS	
Min. Illumination	Color: 0.05Lux @F1.2, B/W: 0.01Lux with IR on	
Lens	3.6mm	
Shutter Time	Auto	
IR Distance	25-30m	
IR Board	15pcs IR LEDs	
White Balance	Auto	
AGC	Auto	
WDR	Digital WDR	
DNR	2D DNR	
BLC	Auto	
HLC	Auto	
Video		
Max. Image Resolution	1080P(1920x1080)	
Frame Rate	Main code stream: 1080P@12.5fps(50HZ),15fps(60HZ) Auxiliary stream:640x352	
Video Compression	Support H.264 Main Profile & H.264 Baseline	

Video Bit Rate	32Kbps-6144Kbps support self-adjustable as needed, default 1024Kbps
Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Support IE, Google, Firefox Browser
Audio	
Audio I/O	No
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, ICMP, SMTP, FTP, DHCP, DNS DDNS,NTP,UPNP,RTSP
WIFI	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
System	
Alarm I/O	Motion detection alarm
Storage	Max support 128GB SD card, timing video storage, motion detection video storage
Motion Detection	4 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox, the pic and video be upload to FTP Server
General	
Working Temperature	-10 °C to 60 °C
Working Humidity	10%-95% (Non-condensing)
Reset	Support
Power Supply	DC12V±10%
Power Consumption	Max 4W
Housing	Vandalproof Dome
Weather Proof	IP66
Language Support	CHN(S)/ENG