

MP-F5DQ200V

2.0MP Network Vandalproof Dome Camera



Model Number	MP-F5DQ200V
Camera	
Image Sensor	1/2.8" color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0Lux with IR on
Lens	2.8-12mm
Shutter Time	Auto
IR Distance	25-30m
IR Board	18pcs SMT LEDs
White Balance	Auto / Manual
AGC	Auto
WDR	Digital WDR
DNR	2D/3D DNR
BLC	support
HLC	support
Video	
Max. Image Resolution	1080P(1920x1080)@25fps
Frame Rate	Main code stream: 1080P/720P/D1@25fps; Auxiliary stream: D1/VGA/640x352/CIF@25fps
Video Compression	H265+/H265/H264

Video Bit Rate	500Kbps-4096Kbps support self-adjustable as needed
Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Internet explorer 6.0 and above (Web Server embedded in device) browser
Audio	
Audio I/O	No
Audio Compression	G.711
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP
ONVIF	ONVIF2.6
APP	Support android, IOS
PC	Support
System	
Alarm I/O	Motion detection alarm
Storage	No
Motion Detection	22*18 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	Support
Action with Alarm	Push to mobile APP
General	
Language Support	CHN(S)/CHN(T)/ENG
Power Supply	DC12V±10%
Power Consumption	Max 4W
Lightning protection	2KV
Housing	Vandalproof Dome
Weather Proof	IP66
Working Temperature	-30 °C to 85 °C
Working Humidity	10%-95% (Non-condensing)