

MP-F5DQ400F-P

4.0MP POE Network Vandalproof Dome Camera



| | |
|-----------------------|--|
| Model Number | MP-F5DQ400F-P |
| Camera | |
| Image Sensor | 1/2.7" color CMOS |
| Min. Illumination | Color: 0.01Lux @F1.2, B/W: 0Lux with IR on |
| Lens | 3.6mm |
| Shutter Time | Auto |
| IR Distance | 25-30m |
| IR Board | 18pcs SMT LEDs |
| White Balance | Auto / Manual |
| AGC | Auto |
| WDR | Digital WDR |
| DNR | 2D/3D DNR |
| BLC | support |
| HLC | support |
| Video | |
| Max. Image Resolution | 4MP (2560*1440)@20fps |
| Frame Rate | Main code stream:4MP@20fps; 3MP@25fps;1080P/720P/D1@30fps; Auxiliary stream: D1/VGA/640x352/CIF@30fps |
| Video Compression | H265+/H265/H264 |

| | |
|----------------------|---|
| Video Bit Rate | 500Kbps-4000Kbps support self-adjustable as needed |
| Image Settings | Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable |
| Bit Superposition | Support OSD name, time and date information superposition |
| Web Access | Internet explorer 6.0 and above (Web Server embedded in device) browser |
| Audio | |
| Audio I/O | No |
| Audio compression | G.711 |
| Network | |
| Network Interface | 1*RJ45 10M/100M Ethernet Port |
| Networking Protocol | TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP |
| ONVIF | ONVIF2.6 |
| APP | Support android, IOS |
| PC | Support |
| System | |
| Alarm I/O | Motion detection alarm |
| Storage | No |
| Motion Detection | 22*18 windows motion detection areas can be setting (sensitivity setting 1-100) |
| Video Mask | Support |
| Action with Alarm | Push to mobile APP |
| General | |
| Language Support | CHN(S)/CHN(T)/ENG |
| POE | IEEE802.3af |
| Power Supply | DC12V±10% / POE |
| Power Consumption | Max 4W |
| Lightning protection | 2KV |
| Housing | Vandalproof Dome |
| Weather Proof | IP67 |
| Working Temperature | -30 °C to 85 °C |
| Working Humidity | 10%-95% (Non-condensing) |