

## MP-L1QI800F-P

8.0MP/4K POE Network Metal Bullet Camera



| Model Number          | MP-L1QI800F-P                                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Camera</b>         |                                                                                                                                                             |
| Image Sensor          | 1/3" SONY color CMOS                                                                                                                                        |
| Min. Illumination     | Color: 0.01Lux @F1.2, B/W: 0.001Lux with IR on                                                                                                              |
| Lens                  | 4.5mm                                                                                                                                                       |
| Shutter Time          | Auto                                                                                                                                                        |
| IR Distance           | 30-35m                                                                                                                                                      |
| IR Board              | 10pcs IR array LEDs                                                                                                                                         |
| White Balance         | Auto / Manual                                                                                                                                               |
| AGC                   | Auto                                                                                                                                                        |
| WDR                   | Digital WDR                                                                                                                                                 |
| DNR                   | 2D/3D DNR                                                                                                                                                   |
| BLC                   | support                                                                                                                                                     |
| HLC                   | support                                                                                                                                                     |
| <b>Video</b>          |                                                                                                                                                             |
| Max. Image Resolution | 8MP(3840*2160)                                                                                                                                              |
| Frame Rate            | Main stream:<br>3840*2160@20fps, 3072*2048/2592*1944/2560*1440/2304*1296/2048*1536/1080P/960P/720P/D1@30fps;<br>Sub stream: 720*480/640*360/CIF@25fps/30fps |

|                      |                                                                                 |
|----------------------|---------------------------------------------------------------------------------|
| Video Compression    | H265 / H264                                                                     |
| Video Bit Rate       | 500Kbps-12Mbps adjustable                                                       |
| Image Settings       | Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable      |
| Bit Superposition    | Support OSD name, time and date information superposition                       |
| Web Access           | Internet explorer 6.0 and above (Web Server embedded in device) browser         |
| <b>Audio</b>         |                                                                                 |
| Audio I/O            | No                                                                              |
| Audio compression    | G.711                                                                           |
| <b>Network</b>       |                                                                                 |
| Network Interface    | 1*RJ45 10M/100M Ethernet Port                                                   |
| Networking Protocol  | TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP                                             |
| ONVIF                | ONVIF2.6                                                                        |
| APP                  | Support android, IOS                                                            |
| PC                   | Support                                                                         |
| <b>System</b>        |                                                                                 |
| Alarm I/O            | No, only motion detection alarm                                                 |
| Advanced Function    | Support WEB Configuration, OSD, Motion detection, etc.                          |
| SIP/VoIP Support     | Yes, Voice & voice-over-IP                                                      |
| Event Trigger        | Motion detection, network disconnection, video masking, etc.                    |
| System Compatibility | ONVIF / CGI Optional                                                            |
| Motion Detection     | 22*18 windows motion detection areas can be setting (sensitivity setting 1-100) |
| Video Mask           | Support                                                                         |
| Action with Alarm    | Push to mobile APP                                                              |
| <b>General</b>       |                                                                                 |
| Language Support     | CHN(S)/CHN(T)/ENG                                                               |
| POE                  | IEEE802.3af                                                                     |
| Power Supply         | DC12V±10% / POE                                                                 |
| Power Consumption    | Max 6W                                                                          |
| Lightning protection | Support                                                                         |
| Housing              | Metal Bullet                                                                    |
| Weather Proof        | IP67                                                                            |
| Working Temperature  | -30 °C to 85 °C                                                                 |
| Working Humidity     | 10%-95% (Non-condensing)                                                        |