

# MP-L2I5I400-WTA2

Smart Wifi Standalone Outdoor SD I TF Card Bullet Camera



<b>Model Number</b>	<b>MP-L2I5I400-WTA2</b>
<b>Camera</b>	
Image Sensor	1/3" color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0.005Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	30-35m
IR Board	2pcs IR array LEDs
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	2D/3D DNR
BLC	Auto
HLC	Auto
<b>Video</b>	
Max. Image Resolution	4MP(2560x1440)
Frame Rate	Main code stream: 4MP@12.5fps(50HZ),15fps(60HZ) Auxiliary stream:800x488/640x352
Video Compression	Support H265, H.264 Main Profile & H.264 Baseline
Video Bit Rate	32Kbps-6144Kbps support self-adjustable as needed, default 2048Kbps

Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Support IE, Google, Firefox Browser
<b>Audio</b>	
Audio I/O	Built-in microphone and speaker
Voice Intercom	Support
Audio Compression	G.711
<b>Network</b>	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPnP, RTSP
WIFI	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
<b>System</b>	
Alarm I/O	Motion detection alarm, Human detection
Storage	Max support 128GB SD card, timing video storage, motion detection video storage
Motion Detection	4 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox, the pic and video be upload to FTP Server
<b>General</b>	
Working Temperature	-10 °C to 60 °C
Working Humidity	10%-95% (Non-condensing)
Reset	Support
Power Supply	DC12V±10%
Power Consumption	Max 4W
Housing	Plastic Bullet with metal front cover
Language Support	CHN(S)/CHN(T)/ENG/KOR/JPN