

MP-L2J5I302-WTA

Smart Wifi Standalone Outdoor SD | TF Card Bullet Camera



Model Number	MP-L2J5I302-WTA
Camera	
Image Sensor	1/2.7" color CMOS,Hisilicon
Min. Illumination	Color: 0.1Lux @F1.2, B/W: 0.01Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	30-35m
IR Board	4pcs IR array leds
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
BLC	Auto
HLC	Auto
Video	
Max. Image Resolution	3MP(2304x1296)@20fps
Frame Rate	Main code stream:3MP(2304x1296)@20fps Auxiliary stream:800x448@20fps
Video Compression	H.265/H.264
Video Bit Rate	32Kbps-6144bps support self-adjustable as needed,default 1024Kbps

Image Settings	Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable
Bit Superposition	Support OSD name,time and date information superposition
Web Access	Support IE,Google,Firefox Browser
Audio	
Audio I/O	1 channel audio input(or according to different cover for choosing)
Audio Compression	G.711
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, TCP, ICMP,UDP,ARP,ICMP,SMTP,FTP,DHCP,DNS DDNS,NTP,UPNP,RTSP
WIFI	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
System	
Alarm I/O	Motion detection alarm
Storage	Max support 128GB SD card,timing video storage,motion detection video storage;
Motion Detection	4 windows motion detection areas can be setting(sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox,the pic and video be upload to FTP Server
General	
Working Temperature	-10 °C to 60 °C
Working Humidity	10%-95% (Non-condensing)
Power Supply	DC12V±10%
Power Consumption	Max 4W
Housing	Outdoor Metal Bullet
Weather Proof	IP67
Language Support	CHN(S)/CHN(T)/ENG/KOR/JPN