

MP-L2K5I400-WTA2

Smart Wifi Standalone Outdoor SD I TF Card Bullet Camera





























Model Number	MP-L2K5I400-WTA2
Camera	
Image Sensor	1/3" color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0.005Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	30-35m
IR Board	2pcs IR array LEDs
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	2D/3D DNR
BLC	Auto
HLC	Auto
Video	
Max. Image Resolution	4MP(2560x1440)
Frame Rate	Main code stream: 4MP@12.5fps(50HZ),15fps(60HZ) Auxiliary stream:800x488/640x352
Video Compression	Support H265, H.264 Main Profile & H.264 Baseline
Video Bit Rate	32Kbps-6144Kbps support self-adjustable as needed, default 2048Kbps

Smart Wifi SD Card Series | MP-L2K5I400-WTA2



	_	
Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable	
Bit Superposition	Support OSD name, time and date information superposition	
Web Access	Support IE, Google, Firefox Browser	
Audio		
Audio I/O	Built-in microphone and speaker	
Voice Intercom	Support	
Audio Compression	G.711	
Network		
Network Interface	1*RJ45 10M/100M Ethernet Port	
Networking Protocol	TCP/IP, HTTP, SMTP, FTP, DHCP, DNS, DDNS, NTP,U PNP, RTSP	
WIFI	WiFi 802.11b/g/n	
ONVIF	ONVIF2.4	
AP Hotspot	Support	
System		
Alarm I/O	Motion detection alarm, Human detection	
Storage	Max support 128GB SD card, timing video storage, motion detection video storage	
Motion Detection	4 windows motion detection areas can be setting (sensitivity setting 1-100)	
Video Mask	4 windows can be built to mask your private area	
Action with Alarm	The alarm pictures be sent to appoint mailbox, the pic and video be upload to FTP Server	
General		
Working Temperature	-10 °C to 60 °C	
Working Humidity	10%-95% (Non-condensing)	
Reset	Support	
Power Supply	DC12V±10%	
Power Consumption	Max 4W	
Housing	Outdoor Metal Bullet	
Weather Proof	IP67	
Language Support	CHN(S)/CHN(T)/ENG/KOR/JPN	