

MP-L8GSI1200M

12MP Auto-Focus Colorful Day&Night Network Metal Bullet Camera



Model Number	MP-L8GSI802M
Camera	
Image Sensor	1/1.7" color SONY CMOS
Day & night mode	FULL COLOR DAY&NIGHT,COLOR: 0.0001LUX@F1.2
Lens	3.6-11mm motorized lens
Shutter Time	Auto / Manual
IR board	NO
White Balance	Auto / Manual
AGC	Auto
WDR	Digital WDR
DNR	2D/3D DNR
BLC	support
HLC	support
Video	
Max. Image Resolution	12MP(4000*3000,4096*2160)
Frame Rate	Main code stream:12MP@15FPS, 8MP/5MP@25/30fps; Auxiliary stream: 720P/D1/VGA@25/30fps
Video Compression	H265+/H265/H264/MJPEG
Video Bit Rate	32Kbps-16Mbps support self-adjustable as needed

Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Internet explorer 6.0 and above (Web Server embedded in device) browser
Audio	
Audio I/O	No
Audio compression	G.711
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	IPv4/IPv6, HTTPS, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP
ONVIF	ONVIF2.6
APP	Support android, IOS
PC	Support
System	
Alarm I/O	Motion detection alarm
Storage	No
Motion Detection	22*18 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	Support
Action with Alarm	Push to mobile APP
General	
Language Support	CHN(S)/CHN(T)/ENG
POE	No
Power Supply	DC12V±10%
Power Consumption	Max 3W
Lightning protection	Support
Housing	Metal bullet
Weather Proof	IP67
Working Temperature	-30 °C to 85 °C
Working Humidity	10%-95% (Non-condensing)