

MP-M9AQ301V

3.0MP Realtime Network Varifocal Metal Dome Camera



Model Number	MP-M9AQ301V
Camera	
Image Sensor	1/2.9" color SONY CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0Lux with IR on
Lens	2.8-12mm varifocal lens
Shutter Time	Auto
IR Distance	25-30m
IR Board	4pcs IR array LEDS
White Balance	Auto / Manual
AGC	Auto
WDR	Digital WDR
DNR	2D/3D DNR
BLC	support
HLC	support
Video	
Max. Image Resolution	3MP (2304*1296) @25fps, 1080P(1920x1080) @30fps
Frame Rate	Main code stream: 3MP@25fps; 1080P/720P/D1@30fps; Auxiliary stream: D1/VGA/640x352/CIF@30fps
Video Compression	H265+/H265/H264
Video Bit Rate	500Kbps-4096Kbps support self-adjustable as needed

Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Internet explorer 6.0 and above (Web Server embedded in device) browser
Audio	
Audio I/O	No
Audio compression	G.711
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP
ONVIF	ONVIF2.6
APP	Support android, IOS
PC	Support
System	
Alarm I/O	Motion detection alarm
Storage	No
Motion Detection	22*18 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	Support
Action with Alarm	Push to mobile APP
General	
Language Support	CHN(S)/CHN(T)/ENG
Power Supply	DC12V±10%
Power Consumption	Max 4W
Lightning protection	2KV
Housing	Metal Dome
Weather Proof	IP66
Working Temperature	-30 °C to 85 °C
Working Humidity	10%-95% (Non-condensing)