

MP-NVR2104M-P4

4CH Single HDD **POE(4 Ports)** Network Digital Video



| | |
|-----------------------------------|--|
| Model | MP-NVR2104M-P4 |
| System | |
| Operating System | Embedded LINUX |
| Video & Audio Input | |
| Bidirectional Talk | N/A |
| Incoming bandwidth | 48Mbps |
| IPC Input | 4CH |
| Video & Audio Output | |
| VGA | 1CH,1920×1080,1280×1024,1280×720,1024×768 |
| HDMI | Standard 1.3a, 1920×1080,1280×1024,1280×720,1024×768 |
| Audio Output | N/A |
| Video & Audio Encoding | |
| Audio Compression | N/A |
| Audio Bit Rate | N/A |
| Video & Audio Decoding | |
| IP channel Resolution | Main stream : up to 1920x2048 Auxiliary stream : D1 |

| | |
|-----------------------|---|
| Video decoding | MPEG-4/H.264(Up to High Profile@Level5.0) |
| Audio decoding | G.711A/G.726 |
| Synchronous Playback | 4CH |
| Decoding Ability | 4CH 720P@30FPS or 2CH 1080P@30FPS |
| Other Function | |
| Bidirectional Talk | N/A |
| Motion Detection | Zones: 396(22*18), Sensitivity : 1~6 (level 6 is the highest) |
| Picture Capture | Support JPEG Capture |
| Intelligent Analysis | N/A |
| Interface | |
| POE Interface | 4CH, IEEE 802.3af, RJ-45 10/100 Mbps self-adaptive Ethernet interface |
| POE Power | ≤45W |
| Network Interface | 1 RJ45 10M/100M self-adaptive Ethernet interface |
| USB Interface | 2 USB2.0 Interfaces |
| Serial Interface | N/A |
| Audio Input / Output | N/A |
| Alarm Input | N/A |
| Alarm Output | N/A |
| Storage | |
| SATA | 1*SATA HDD |
| Capacity | Unlimited |
| Network | |
| Network Protocols | IPV4, TCP, UDP, RTSP, HTTP, DNS, DDNS, DHCP, NTP, SMTP, UPNP |
| Format | |
| Video Compression | H.265 + /H.265(HEVC)/H.264 + /H.264 |
| General | |
| Compatibility | ONVIF |
| Dimensions | 410*293*60mm |
| Size | 215*235*45mm |
| Weight | 1KG (without HDD) |
| Installation | Desktop Installation |
| Power Supply | DC 48V 1.35A |
| Consumption | 5W(without HDD) |
| Working Conditions | Temperature: -0°C-- +55°C Humidity: 10%~90% |

