

MP-NVR6108MS

8CH Single HDD Network Digital Video Recorder



Model	MP-NVR6108MS
System	
Operating System	Embedded LINUX
Video & Audio Input	
Bidirectional Talk	1CH, RCA (Line in,2Vp-p,1Kohms)
Incoming bandwidth	60Mbps
IPC Input	8CH
Video & Audio Output	
VGA	1CH,1920×1080,1280×1024,1280×720,1024×768
HDMI	Standard 1.4a, 3840×2160,1920×1080,1280×1024,1280×720,1024×768
Audio Output	1CH, RCA (Line out,2Vp-p,300ohms)
Video & Audio Encoding	
Audio Compression	G.711A
Audio Bit Rate	64Kbps
Video & Audio Decoding	
IP channel Resolution	Main stream: up to 2560x1920 Auxiliary stream: D1

Video decoding	H.265(Main Profile@L5.0 High-tie)/H.264 Up to High Profile@Level5.0
Audio decoding	G.711A/G711U/ACC
Synchronous Playback	8CH
Decoding Ability	4CH 1080P@30FPS
Other Function	
Bidirectional Talk	Two-way voice intercom function
Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is the highest)
Picture Capture	Support JPEG Capture
Intelligent Analysis	1CH Face detection or 1CH Perimeter detection, Up to 1080P
Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface
USB Interface	1 USB2.0 Interface, 1 USB3.0 Interface
Serial Interface	N/A
Audio Input / Output	1CH, RCA (Line out,2Vp-p,300ohms)
Alarm Input	N/A
Alarm Output	N/A
Storage	
SATA	1*SATA HDD
Capacity	Unlimited
Network	
Network Protocols	IPV4, TCP, UDP, RTSP, HTTP, DNS, DDNS, DHCP, NTP, SMTP, UPNP
Format	
Video Compression	H.265 + /H.265(HEVC)/H.264 + /H.264
General	
Compatibility	ONVIF
Dimensions	250*355*55mm
Size	215*215*50mm
Weight	0.9Kg (without HDD)
Installation	Desktop Installation
Power Supply	DC 12V 2A
Consumption	7W(without HDD)
Working Conditions	Temperature: -10°C~+55°C Humidity: 10%~90%