

## MP-Q1VQ201F

2.0MP Network Plastic Dome Camera



| Model Number          | MP-Q1VQ201F                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------|
| Camera                |                                                                                               |
| Image Sensor          | 1/2.8" color SONY CMOS                                                                        |
| Min. Illumination     | Color: 0.01Lux @F1.2, B/W: 0Lux with IR on                                                    |
| Lens                  | 3.6mm                                                                                         |
| Shutter Time          | Auto                                                                                          |
| IR Distance           | 20-25m                                                                                        |
| IR Board              | 15pcs IR leds                                                                                 |
| White Balance         | Auto / Manual                                                                                 |
| AGC                   | Auto                                                                                          |
| WDR                   | Digital WDR                                                                                   |
| DNR                   | 2D/3D DNR                                                                                     |
| BLC                   | support                                                                                       |
| HLC                   | support                                                                                       |
| Video                 |                                                                                               |
| Max. Image Resolution | 3MP(2304*1296)@25fps,1080P(1920x1080)@30fps                                                   |
| Frame Rate            | Main code stream:3MP@25fps;1080P/720P/D1@30fps;<br>Auxiliary stream: D1/VGA/640x352/CIF@30fps |
| Video Compression     | H265+/H265/H264                                                                               |

|                      |                                                                                |
|----------------------|--------------------------------------------------------------------------------|
| Video Bit Rate       | 500Kbps-4096Kbps support self-adjustable as needed                             |
| Image Settings       | Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable          |
| Bit Superposition    | Support OSD name,time and date information superposition                       |
| Web Access           | Internet explorer 6.0 and above (Web Server embedded in device) browser        |
| <b>Audio</b>         |                                                                                |
| Audio I/O            | No                                                                             |
| Audio compression    | G.711                                                                          |
| <b>Network</b>       |                                                                                |
| Network Interface    | 1*RJ45 10M/100M Ethernet Port                                                  |
| Networking Protocol  | TCP/IP, HTTP,RTSP,DHCP,NTP,UPNP                                                |
| ONVIF                | ONVIF2.6                                                                       |
| APP                  | Support android, IOS                                                           |
| PC                   | Support                                                                        |
| <b>System</b>        |                                                                                |
| Alarm I/O            | Motion detection alarm                                                         |
| Storage              | No                                                                             |
| Motion Detection     | 22*18 windows motion detection areas can be setting(sensitivity setting 1-100) |
| Video Mask           | Support                                                                        |
| Action with Alarm    | Push to mobile APP                                                             |
| <b>General</b>       |                                                                                |
| Language Support     | CHN(S)/CHN(T)/ENG                                                              |
| Power Supply         | DC12V±10%                                                                      |
| Power Consumption    | Max 4W                                                                         |
| Lightning protection | 2KV                                                                            |
| Housing              | Plastic Dome                                                                   |
| Weather Proof        | N/A                                                                            |
| Working Temperature  | -30 °C to 85 °C                                                                |
| Working Humidity     | 10%-95% (Non-condensing)                                                       |